



MAGNET ELEVATOR ME-09



Description:

The ME-09 magnet elevator is a perfect supply of metal lids to the TO-05 Twist-off machine. The stock bunker is filled with metal lids. The lids are transported upwards by a magnetic elevator belt. Depending on het capacity there is a sensor that detects the lids. The lids that are wrong are blown off the magnetic belt and fall back into the stock bunker. The remaining lids are guided through a guide to feed the twist-off machine. The machine is easy to empty before changing to a different lid format.

Film: LVS Magnet Elevator Belt 09 - YouTube

Advantages:

This very stable and robust machine is extremely user friendly and easily accessible for adjustment, maintenance and cleaning.

Perfect supply for the Twist-off machine.

ME-09-06 type works without using compressed air.

Options:

For even faster changing to other lids the ME-09-12 and ME-09-18 can be delivered with a 3 compartment stock magazine. Extension when the elevator belt cannot stand directly next to the TO-machine.

The ME-09-12 and ME-09-18 are available in left and right version.

Lenssen Vul en Sluittechniek BV, Berghemweg 23, 5975 RJ, Sevenum, Nederland Tel: +31 475594869, Mail: info@lvs-bv.nl


Website: www.lvs-bv.nl





Technical data			
Model	ME-09-06	ME-09-12	ME-09-18
Max Capacity	100/min	200/min	300/min
Lid supply	Elevator	Elevator	
Max speed	45 meter/min	90 meter/min	140 meter/min
Lid diameter	TO-027 - TO-110		
Electrical connection	240 Volt - 50 Hz - 0,37kW	240 Volt - 50 Hz - 0,75kW	
Compressed air	6 bar		
Storage bin	100 liter	400 liter	
Dimensions (L x B x H)	800 x 600 x 2700 mm	1000 x 800 x 3300 mm	
Weight	Ca. 225 kg	Ca. 250 kg	

ME-09-06



ME-09-12/18

